

## RV Load Inflation Tables

### TIRE LOAD LIMITS (LBS.) AT VARIOUS COLD INFLATION PRESSURES

• NEVER exceed the sidewall markings for the maximum loads and inflation pressures

Note: Letters in parentheses indicate the Load Range for which Bold Face loads are maximum

Tire Size	PSI	35	40	45	50	55	60	65	70	75	80	
LT225/75R16	Dual	lbs.	1365	1500	1630	<b>1765(C)</b>	1875	1995	<b>2150(D)</b>	2220	2330	<b>2470(E)</b>
	Single	lbs.	1500	1650	1790	<b>1940(C)</b>	2060	2190	<b>2335(D)</b>	2440	2560	<b>2680(E)</b>
LT215/85R16	Dual	lbs.	1360	1490	1625	<b>1765(C)</b>	1865	1985	<b>2150(D)</b>	2210	2320	<b>2470(E)</b>
	Single	lbs.	1495	1640	1785	<b>1940(C)</b>	2050	2180	<b>2335(D)</b>	2430	2550	<b>2680(E)</b>
LT235/85R16	Dual	lbs.	1545	1700	1845	<b>2006(C)</b>	2125	2260	<b>2381(D)</b>	2515	2645	<b>2778(E)</b>
	Single	lbs.	1700	1870	2030	<b>2205(C)</b>	2235	2485	<b>2623(D)</b>	2765	2905	<b>3042(E)</b>

Warning! Never mount a 16" size diameter tire on a 16.5" rim.

Tire Size	PSI	70	75	80	85	90	95	100	105	110	115	120	125	130	
215/75R17.5	Dual	lbs.	2550	2695	2835	2980	3120	3255	3390	<b>3530(G)</b>					
	Single	lbs.	2710	2865	3015	3165	3310	3460	3605	<b>3750(G)</b>					
225/70R19.5	Dual	lbs.	2720	2860	<b>3000(E)</b>	3115	3245	<b>3415(F)</b>							
	Single	lbs.	2895	3040	<b>3195(E)</b>	3315	3450	<b>3640(F)</b>							
245/70R19.5	Dual	lbs.			3415	3515	3655	<b>3860(F)</b>	3940	4075	<b>4300(G)</b>	4345	<b>4540(H)</b>		
	Single	lbs.			3640	3740	3890	<b>4080(F)</b>	4190	4335	<b>4540(G)</b>	4620	<b>4805(H)</b>		
265/70R19.5	Dual	lbs.			3750	3930	4095	4300	4405	4415	<b>4675(G)</b>				
	Single	lbs.			3970	4180	4355	4540	4685	4850	<b>5070(G)</b>				
285/70R19.5	Dual	lbs.			4200	4410	4615	4820	5020	5220	5420	5615	5810	<b>6005(H)</b>	
	Single	lbs.			4470	4695	4915	5130	5345	5560	5770	5980	6185	<b>6395(H)</b>	
8R19.5	Dual	lbs.	2460	2570	<b>2680(D)</b>	2785	2890	<b>3000(E)</b>	3100	3200	<b>3305(F)</b>				
	Single	lbs.	2540	2680	<b>2835(D)</b>	2955	3075	<b>3195(E)</b>	3305	3415	<b>3525(F)</b>				
255/70R22.5	Dual	lbs.			3970	4110	4275	4410	4455	4610	<b>4675(G)</b>	4915	<b>5070(H)</b>		
	Single	lbs.			4190	4370	4550	4675	4895	5065	<b>5205(G)</b>	5400	<b>5510(H)</b>		
275/70R22.5	Dual	lbs.	3895	4115	4335	4550	4765	4975	5180	5390	5590	5795	5995	6195	<b>6395(H)</b>
	Single	lbs.	4230	4470	4705	4940	5175	5400	5630	5850	6075	6295	6510	6730	<b>6945(H)</b>
245/75R22.5*	Dual	lbs.	3160	3315	3525	3615	3765	3970	4055	4195	<b>4300(G)</b>				
	Single	lbs.	3470	3645	3860	3975	4140	4300	4455	4610	<b>4675(G)</b>				
265/75R22.5**	Dual	lbs.	3525	3705	3860	4040	4205	4410	4525	4685	<b>4805(G)</b>				
	Single	lbs.	3875	4070	4300	4440	4620	4805	4975	5150	<b>5205(G)</b>				
295/75R22.5***	Dual	lbs.	4095	4300	4540	4690	4885	<b>5070(F)</b>	5260	5440	<b>5675(G)</b>				
	Single	lbs.	4500	4725	4940	5155	5370	<b>5510(F)</b>	5780	5980	<b>6175(G)</b>				
295/80R22.5	Dual	lbs.	4360	4610	4855	5095	5335	5570	5805	6035	6265	6490	6715	<b>6940(H)</b>	
	Single	lbs.	4920	5200	5475	5750	6020	6285	6545	6810	7065	7320	7575	<b>7830(H)</b>	
315/80R22.5	Dual	lbs.	5035	5325	5605	5885	6160	6430	6700	6970	7235	7495	7755	8010	<b>8270(L)</b>
	Single	lbs.	5535	5850	6160	6470	6770	7070	7365	7660	7950	8240	8525	8805	<b>9090(L)</b>
9R22.5	Dual	lbs.	3270	3410	3550	3690	<b>3860(E)</b>	4005	4150	<b>4300(F)</b>					
	Single	lbs.	3370	3560	3730	3890	<b>4080(E)</b>	4235	4390	<b>4540(F)</b>					
10R22.5	Dual	lbs.	3860	4045	4230	<b>4410(E)</b>	4585	4760	<b>4940(F)</b>	5075	5210	<b>5355(G)</b>			
	Single	lbs.	4080	4280	4480	<b>4675(E)</b>	4850	5025	<b>5205(F)</b>	5360	5515	<b>5675(G)</b>			
11R22.5	Dual	lbs.	4380	4580	4760	4950	<b>5205(F)</b>	5415	5625	<b>5840(G)</b>	5895	5950	<b>6005(H)</b>		
	Single	lbs.	4530	4770	4990	5220	<b>5510(F)</b>	5730	5950	<b>6175(G)</b>	6320	6465	<b>6610(H)</b>		
12R22.5****	Dual	lbs.	4780	4990	5190	5390	<b>5675(F)</b>	5785	5895	<b>6005(G)</b>	6265	6525	<b>6780(H)</b>		
	Single	lbs.	4940	5200	5450	5690	<b>6005(F)</b>	6205	6405	<b>6610(G)</b>	6870	7130	<b>7390(H)</b>		
285/75R24.5	Dual	lbs.	4135	4340	4540	4740	4930	<b>5205(F)</b>	5310	5495	<b>5675(G)</b>	5860	<b>6175(H)</b>		
	Single	lbs.	4545	4770	4940	5210	5420	<b>5675(F)</b>	5835	6040	<b>6175(G)</b>	6440	<b>6780(H)</b>		
11R24.5	Dual	lbs.	4660	4870	5070	5260	<b>5510(F)</b>	5675	5840	<b>6005(G)</b>	6205	6405	<b>6610(H)</b>		
	Single	lbs.	4820	5070	5310	5550	<b>5840(F)</b>	6095	6350	<b>6610(G)</b>	6790	6970	<b>7160(H)</b>		

Warning! Wheels are stamped with the maximum permissible load and inflation. Never exceed the load or inflation rating of the wheel!

Warning! Always inflate tire/wheel assemblies in an OSHA approved tire safety cage. Use a clip-on air hose and extension. Stand well back from the tire during inflation due to the risk of explosion of the tire/wheel assembly.

\*Equivalent to Michelin 235/80R22.5

\*\*Equivalent to Michelin 255/80R22.5

\*\*\*Equivalent to Michelin 275/80R22.5

\*\*\*\*Equivalent to Michelin 295/80R22.5

NOTE: All data shown here is approximately what you would find under normal conditions and is subject to change without notice.

Though every effort has been taken to ensure the accuracy of this data shown here, legal responsibility cannot be accepted by Toyo Tire (U.S.A.) Corp. or Toyo Tire & Rubber Co., Ltd., for any damage or loss coming from any undetected errors or any misprint.