

TOYO TIRES[®]

LIGHT TRUCK TIRES

*Any road, any
terrain.*



TOYO TIRES[®]
driven to perform



OPEN COUNTRY® Q/T ***SUV/CUV All Season Touring***

Designed to offer a quiet comfortable ride while also providing added load carrying capacity needed for SUV and CUV vehicles.



ASYMMETRIC TREAD DESIGN

- >> Outside of the tire for cornering, center for braking, accelerating and traction, and the inside edge of the tire for stability and traction.
- >> Enables cross rotation to reduce irregular wear.



CENTRE STABILIZER RIB

- >> Ensures a comfortable ride on dry roads and stability while driving at higher speeds.



4 CIRCUMFERENTIAL GROOVES

- >> 4 wide grooves help evacuate water and slush for added traction during inclement weather.



LARGE OUTER BLOCKS

- >> Helps propel the vehicle through mud, slush and snow.

Offers a quiet, comfortable ride; impressive tread life; and attractive design.





OPEN COUNTRY H/T[®]

Highway All Season

An all season, light truck tire designed for optimal ride comfort, performance and handling during city and highway use. Ideal for light truck, SUV or crossover vehicles.


DEEP WATER EVACUATION GROOVES

>> For excellent road surface grip, cooler running and longer tread life.




VARIABLE-PITCH DESIGN

>> Block pitch pattern distributed non-sequentially to enhance noise reduction.



MULTI-WAVE SIPES

>> Multi-wave sipes appear as the tire wears and interlocks to help decrease block movement for increased resistance to irregular wear.



LARGE RIGID SHOULDER BLOCKS

>> For increased rigidity for improved cornering and braking. Reduces irregular wear, improving ride comfort.



A larger contact area and more evenly distributed contact pressure result in better wear.




OPEN COUNTRY® A/T II *On or Off Road All Terrain*

With improved tread wear over its predecessor, backed with a comprehensive tread wear warranty, it's as close to invincible as an all terrain tire can get.




POLYGONAL BLOCKS AND ZIGZAG SIPES

>> Excellent all season performance.




DEEP TREAD GROOVES WITH STONE EJECTING BLOCKS / TAPERED CLAW EDGES

>> For enhanced mud and snow traction.



TIE BARS BETWEEN BLOCKS

>> Stabilize tread blocks to reduce irregular wear and road noise.
>> Improved braking.



WEAR-RESISTANT TREAD COMPOUND

>> Excellent tread life and durability.
>> UTQG 600A B (S and T rated, P-Metric)
>> UTQG 600A A (H rated, P-Metric)

LT and Flotation sizes feature a rugged look with an aggressive, deeper tread and heavy duty construction.





OPEN COUNTRY® A/T II

All Weather - All Terrain

The same great on or off road traction, ride comfort and reliability SUVs and pick-up truck owners have become accustomed to with the Toyo Open Country AT II but now certified for winter service!*

WIDE EVACUATION GROOVES

>> Helps to quickly propel dirt mud and snow from the center of the tire for added traction.



TAPERED CLAW EDGES

>> These edges within the tread grooves enhance traction in deep mud, snow or slush.



DEEP TREAD GROOVES

>> These large deep grooves improve traction on wet roads and also allow the tire to dig into mud, slush or snow.



INCREASED 3D SIPE DENSITY

>> Increased sipe density throughout the tread blocks add edge grip on ice and slippery surfaces.

>> Toyo's multi-wave 3D sipes reduce the chance of block movement for better wet and dry performance with less chance irregular wear.



Now with the security of all weather traction!*



*select sizes



OPEN COUNTRY® A/T II **XTREME**

The "XTREME" series of Open Country A/T II light truck tires give you all the traction you need with more durability and longevity than the competition.



XTREME SERIES SIZES

>> "XTREME" series sizes feature a deep scalloped shoulder and heavy duty construction for a rugged aggressive look and added durability for those Xtreme conditions!




AGGRESSIVE SIDEWALL AND OPEN TREAD BLOCK DESIGN

>> Delivers tough looks and even tougher performance in dirt, mud or snow, while maintaining a quiet ride.



POLYGONAL BLOCKS AND ZIGZAG SIPES

>> Excellent all season performance.



DEEP TREAD GROOVES WITH STONE EJECTING BLOCKS / TAPERED CLAW EDGES

>> For enhanced mud and snow traction.

All the features of the popular Open Country A/T II with added performance, looks and durability!





OPEN COUNTRY C/T

All Weather - Heavy Duty



Designed for on or off road driving conditions combining winter performance with commercial durability and traction.

CUT AND CHIP RESISTANT COMPOUNDING

>> Resists cutting and chipping while remaining flexible for enhanced grip and traction in winter conditions.



DEEP GROOVES AND STONE EJECTORS

>> Elevated stone ejectors are optimally positioned throughout the tread grooves to dislodge stones that may penetrate the tread.



AGGRESSIVE SIDEWALL AND BUTTRESS

>> For tough looks and even tougher performance in dirt, mud or snow.



DUAL-ANGLE SHOULDER BLOCKS

>> Designed to enhance traction in snow, mud and rutted road conditions.



All weather,
advanced
heavy duty
construction!





OPEN COUNTRY® R/T

On/Off Road Rugged Terrain

A revelation in technology for light truck and SUVs. Not only designed to be aggressive in off-road adventures. They also provided a smoother on road driving experience.

BLOCK DESIGN BUILT FROM LEGENDS

- >> The aggressive outside block design is inspired by the aggressive Open Country M/T for added off-road traction.
- >> The inner blocks are inspired from the aggressive yet smooth running Open Country A/T II for great looks and added ride comfort.

ALTERNATING SHOULDER BLOCK DESIGN

- >> By alternating the shoulder blocks between scalloped and square increases traction ability during rugged off road driving.

FULL LATERAL GROOVES

- >> The full lateral grooves help improve the evacuation and mud in off-road conditions and moisture during on road driving for better traction no matter what the road surface.

Off-road performance meets on road comfort!





OPEN COUNTRY M/T ***Maximum Traction Off Road***

Designed to increase the vehicle's off highway performance while giving it an enhanced and rugged look.


OVER-THE-SHOULDER ALTERNATING CURVED TREAD

>> Helps to bite into the ground and eject mud and rocks while giving extra grip in deep sand or mud.



DEEP ANGLED SIPES

>> Sipes help increase edge effect on slippery surfaces. Deep sipes ensure extra traction for the life of the tire.




DEEP OPEN TREAD DESIGN

>> For improved grip and dispersion in the wet or mud. Added tread depth increases the tire life.



AGGRESSIVE ATTACK TREAD DESIGN WITH HOOK SHAPED BLOCKS

>> Delivers enhanced off road traction and great on road performance.



Built to be aggressive yet with style!




M-55

On or Off Road Commercial Traction



The M-55 is an all position traction radial designed to deliver versatility and exceptional mileage with dependable traction on or off road.



KNOWN WORLDWIDE FOR ITS WILLINGNESS TO TAKE ON THE TOUGHEST OF TASKS

- >> Tough, wide steel-belted construction.
- >> Polyester casing.



OPEN SHOULDER DESIGN

- >> Maximizes water evacuation for excellent all terrain traction and stability.



NUMEROUS SIPES

- >> Improves water evacuation and ice traction.




AGGRESSIVE LUG AND BLOCK TREAD DESIGN

- >> Provides solid handling and traction.

Solid, ON or OFF road traction in all weather conditions.

* select sizes





OPEN COUNTRY **WLT1**

Winter Heavy Duty



Engineered to deliver optimal performance for a variety of commercial vehicle applications in demanding winter road conditions.

HEAVY DUTY CONSTRUCTION WITH A STIFF RIGID CASING

>> Designed for the unique load carrying, handling and braking requirements of light truck and commercial van applications.

STRAIGHT SIPE & DIMPLE DESIGN ON THE OUTSIDE OF THE TREAD

>> For resistance to wandering and improved snow traction in deep snow.

INCREASED SIPE DENSITY

>> Improves water evacuation and ice traction.

WIDER AND DEEPER GROOVES

>> For increased snow traction.
>> Self-cleaning pocket for effective snow drainage.



Built to handle a tough load in tough winter conditions!



TOYO H09

All Weather Commercial Traction

The Toyo H09 was developed for commercial cargo vans that operate in a variety of conditions.

The Toyo H09 is a euro-metric "all weather" tire designed for commercial van drivers who need the added winter safety during unexpected snow falls and cold weather conditions but don't want to incur the expense of buying, installing and storing winter tires.

- >> MEETS LOAD CARRYING REQUIREMENTS of today's commercial cargo vans.
- >> SAFER on snow and ice compared to a traditional all-season tire
- >> CONVENIENT for a consumer who doesn't want the expense of buying, installing and storing winter tires.

TOYO H09

SIZE	SD	SW	1/32"	OD	OW	SLR	RPK
16 235/65R16C	121/119R	BL 10-E	13	28.0	9.4	12.7	460

"Millennium" warranty:
- 5 year workmanship and materials.

Solid, ON or OFF road traction in all weather conditions.

* select sizes



OPEN COUNTRY® Q/T

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
16	215/70R16	100H	BL	680AA	12	27.9	8.7	12.6	463
	225/70R16	103H	BL	680AA	12	28.4	9.0	12.8	454
	P235/70R16	104T	BL	680AB	12	29.0	9.4	13.1	445
	255/65R16	109H	BL	680AA	13	29.1	10.2	13.1	444
17	P265/70R17	113H	BL	680AA	13	31.7	10.7	14.2	408
	225/65R17	102H	BL	680AA	12	28.5	9.0	13.0	453
	235/65R17	XL 108V	BL	680AA	12	29.1	9.4	13.2	444
	P245/65R17	105H	BL	680AA	13	29.5	9.8	13.4	437
	P265/65R17	110S	BL	680AB	13	30.6	10.7	13.8	423
	235/60R17	102T	BL	680AB	12	28.1	9.4	12.8	459
	255/60R17	106V	BL	680AA	12	29.1	10.2	13.2	444
18	235/65R18	106V	BL	680AA	12	30.0	9.4	13.7	430
	P255/65R18	109S	BL	680AB	13	31.1	10.2	14.1	416
	P265/65R18	112H	BL	680AA	13	31.5	10.7	14.3	409
	235/60R18	XL 107V	BL	680AA	12	29.1	9.4	13.3	444
	245/60R18	105H	BL	680AA	13	29.6	9.8	13.5	437
	255/60R18	XL 112V	BL	680AA	12	30.0	10.2	13.7	430
	265/60R18	110V	BL	680AA	12	30.5	10.7	13.9	423
	235/55R18	100V	BL	680AA	12	28.1	9.6	13.0	459
	255/55R18	XL 109V	BL	680AA	12	29.0	10.4	13.3	445
19	255/60R19	109H	BL	680AA	13	31.1	10.2	14.2	416
	P225/55R19	99V	BL	680AA	12	28.8	9.2	13.3	449
	235/55R19	XL 105V	BL	680AA	12	29.2	9.6	13.5	442
	P245/55R19	103H	BL	680AA	13	29.6	10.0	13.7	435
	255/55R19	XL 111V	BL	680AA	12	30.0	10.4	13.8	430
	275/55R19	111V	BL	680AA	12	30.9	11.2	14.1	418
	235/50R19	99H	BL	680AA	12	28.3	9.6	13.1	456
	235/50R19	XL 106V	BL	680AA	12	28.3	9.6	13.1	456
	255/50R19	XL 107V	BL	680AA	12	29.1	10.4	13.4	444
	265/50R19	XL 110V	BL	680AA	12	29.5	10.9	13.6	438
20	235/55R20	102V	BL	680AA	12	30.2	9.6	14.0	428
	255/55R20	XL 110V	BL	680AA	12	31.0	10.4	14.3	416
	P245/50R20	102V	BL	680AA	12	29.7	10.0	13.8	435
	255/50R20	XL 109V	BL	680AA	12	30.1	10.4	13.9	429
22	P265/50R20	XL 111V	BL	680AA	12	30.5	10.9	14.1	424
22	P285/45R22	110H	BL	680AA	12	32.1	11.2	14.9	402



"Millennium" warranty: - 105,000 km warranty
- 5 year workmanship and materials.

XL - Extra Load

An attractive sidewall that is built to handle the unique load carrying needs of these types of vehicles that not only adds to the look of your SUV or CUV, but is also designed to ensure performance is not compromised.



Tire data subject to change. Visit toyotires.ca for current data.

LEGEND

SIZE - Tire Size SD - Service Description OW - Overall Width RPK - Revolutions
SW - Side Wall OD - Overall Diameter SLR - Standard Load Radius Per Kilometer

OPEN COUNTRY H/T®

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
15	P225/75R15	102S	OWL	640A B	13	28.3	8.9	12.7	455
	P235/75R15	105S	OWL	640A B	13	28.9	9.3	12.9	447
	P225/70R15	100T	OWL	640A B	13	27.4	8.9	12.4	470
	P235/70R15	102S	OWL	640A B	13	28.0	9.4	12.6	462
	P265/70R15	110S	BL	640A B	13	29.6	10.4	13.2	436
	LT235/75R15	104S	OWL	6-C	14	28.8	9.5	12.9	449
	31x10.50R15LT	109S	OWL	6-C	16	30.3	10.9	13.5	426
16	P225/75R16	104S	OWL	640A B	13	29.3	8.9	13.2	440
	P235/75R16	106S	OWL	640A B	13	29.8	9.4	13.4	433
	P245/75R16	109S	OWL	640A B	13	30.4	9.8	13.6	424
	P265/75R16	114T	OWL	640A B	13	31.5	10.4	14.1	409
	P215/70R16	99H	BL	640A A	12	27.9	8.7	12.6	462
	P225/70R16	101T	OWL	640A B	13	28.4	9.0	12.8	454
	P235/70R16	104T	OWL	640A B	13	28.9	9.3	13.0	446
	P245/70R16	106S	OWL	640A B	13	29.4	9.6	13.2	439
	P255/70R16	109S	OWL	640A B	13	30.0	10.1	13.5	430
	P265/70R16	111S	OWL	640A B	13	30.6	10.4	13.7	421
	P275/70R16	114H	BL	640A A	13	31.2	11.0	13.9	414
	215/65R16	98H	BL	640A A	12	27.0	8.8	12.3	478
	P235/65R16	101S	BL	640A B	12	28.0	9.6	12.7	460
	255/65R16	109H	BL	640A A	13	29.1	10.2	13.1	444
	235/60R16	100H	BL	640A A	12	27.1	9.4	12.3	477
	LT215/85R16	115S	BL	10-E	15	30.4	8.9	13.6	424
LT235/85R16	120S	OWL	10-E	15	31.8	9.4	14.1	406	
LT225/75R16	115S	BL	10-E	14	29.3	9.1	13.1	441	
LT245/75R16	120S	OWL	10-E	15	30.4	9.9	13.6	424	
LT265/75R16	123S	OWL	10-E	16	31.6	10.8	14.1	409	
17	P235/75R17	108S	OWL	640A B	13	30.9	9.5	13.9	418
	P245/75R17	110S	OWL	640A B	13	31.5	9.8	14.2	410
	P235/70R17	XL 108S	BL	640A B	13	29.9	9.4	13.5	432
	P235/70R17	XL 108S	OWL	640A B	13	29.9	9.4	13.5	432
	P245/70R17	108S	BL	640A B	13	30.4	9.8	13.7	425
	P245/70R17	108S	OWL	640A B	13	30.6	9.8	13.8	423
	P255/70R17	110S	BL	640A B	13	31.1	10.3	14.0	415
	P255/70R17	110S	OWL	640A B	13	31.1	10.3	14.0	415
	P265/70R17	113T	BL	640A B	13	31.5	10.8	14.1	410
	P265/70R17	113T	OWL	640A B	13	31.5	10.7	14.2	409
	P285/70R17	117T	BL	640A B	14	32.7	11.4	14.6	395
	225/65R17	102H	BL	640A A	12	28.5	8.9	13.0	453
	235/65R17	104H	BL	640A A	12	29.1	9.4	13.2	443
	235/65R17	XL 108V	OWL	640A A	12	29.0	9.4	13.2	445
	P245/65R17	105H	BL	640A A	13	29.5	9.7	13.4	437
	P245/65R17	105H	OWL	640A A	13	29.5	9.7	13.4	437
	P255/65R17	108S	BL	640A B	13	30.1	10.4	13.6	429
	P255/65R17	108S	OWL	640A B	13	30.1	10.3	13.6	429
	P265/65R17	110S	BL	640A B	13	30.6	10.8	13.8	423
	P265/65R17	110S	OWL	640A B	13	30.5	10.6	13.7	424
	275/65R17	115T	OWL	640A B	13	31.1	11.0	14.0	415
	P235/60R17	100S	BL	640A B	12	28.2	9.4	12.9	458
	P235/60R17	100S	OWL	640A B	11	28.2	9.4	12.9	458
	255/60R17	106H	BL	640A A	13	29.1	10.3	13.2	444
	235/55R17	99H	BL	640A A	13	27.2	9.4	12.5	475
	LT235/80R17	120S	BL	10-E	15	31.7	9.2	14.3	407
	LT245/75R17	121S	BL	10-E	15	31.5	9.8	14.2	410
	LT245/75R17	121S	OWL	10-E	15	31.5	9.9	14.2	410
LT245/70R17	119S	BL	10-E	15	30.6	9.9	13.8	421	
LT245/70R17	119S	OWL	10-E	15	30.5	9.8	13.8	423	
LT265/70R17	121S	BL	10-E	16	31.7	10.8	14.2	407	
LT265/70R17	121S	OWL	10-E	16	31.6	10.7	14.2	409	
LT285/70R17	121S	OWL	10-E	17	32.7	11.7	14.6	395	
18	255/70R18	113S	BL	640A B	12	32.2	10.4	14.5	401
	P265/70R18	114S	BL	640A B	13	32.6	10.8	14.7	395
	P265/70R18	114S	OWL	640A B	13	32.6	10.8	14.7	395
	P235/65R18	104T	BL	640A B	12	30.2	9.6	13.7	428
	P255/65R18	109S	BL	640A B	12	31.1	10.2	14.1	416
	P265/65R18	112S	BL	640A B	13	31.5	10.7	14.3	410
	P275/65R18	114T	BL	640A B	13	32.2	11.0	14.5	401
	P275/65R18	114T	OWL	640A B	13	32.2	11.0	14.5	401
	235/60R18	XL 107V	BL	640A A	11	29.1	9.4	13.3	444
	P245/60R18	104H	BL	640A A	13	29.6	9.6	13.5	435
	255/60R18	XL 112H	BL	640A A	13	30.0	10.1	13.7	430
	P265/60R18	109T	BL	640A B	13	30.5	10.8	13.9	423
	P265/60R18	109T	OWL	640A B	13	30.5	10.6	13.9	424

OPEN COUNTRY H/T®

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
18	P275/60R18	111H	BL	640A A	13	30.8	10.9	14.0	419
	235/55R18	100V	BL	640A A	10	28.1	9.6	13.0	459
	255/55R18	XL 109V	BL	640A A	12	29.1	10.4	13.3	444
	LT275/70R18	125S	BL	10-E	16	33.1	11.2	14.9	390
	LT275/70R18	125S	OWL	10-E	16	33.1	11.1	14.9	390
	LT275/65R18	123S	BL	10-E	16	32.0	10.9	14.4	404
	LT275/65R18	123S	OWL	10-E	16	32.0	10.9	14.4	404
19	255/60R19	109H	BL	640A A	13	31.1	10.2	14.2	416
	P245/55R19	103S	BL	640A B	13	29.7	9.6	13.7	435
	255/55R19	XL 111V	BL	640A A	12	30.0	10.4	13.8	430
20	P275/60R20	114S	OWL	640A B	13	33.1	10.9	15.1	390
	P235/55R20	102T	BL	640A B	13	30.2	9.4	14.0	427
	P255/55R20	107H	BL	640A A	13	31.0	10.4	12.1	416
	275/55R20	XL 117S	OWL	640A B	13	31.9	11.4	14.6	405
	P245/50R20	102V	BL	640A A	12	29.7	10.0	11.6	435
	265/50R20	XL 111V	BL	640A A	11	30.4	10.9	14.1	424
22	285/45R22	XL 114H	BL	640A A	12	32.0	11.2	14.9	403



"Millennium" warranty: - 100,000 km treadwear limited warranty (P-metric sizes)
- 5 year workmanship and materials.

XL - Extra Load

P-Metric & Metric Sizes

OPEN COUNTRY A/T II

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
15	P215/75R15	100S	BL	600A B	12	27.7	8.5	12.4	466
	P225/75R15	102S	OWL	600A B	13	28.3	8.8	12.7	456
	P235/75R15	XL 108S	OWL	600A B	13	28.9	9.3	12.9	447
	P265/75R15	112S	OWL	600A B	13	30.7	10.5	13.6	421
16	P225/75R16	104S	BL	600A B	13	29.3	8.8	13.2	441
	P245/75R16	109S	OWL	600A B	13	30.5	9.8	13.6	424
	P265/75R16	114T	BL	600A B	13	31.7	10.5	14.1	408
	P265/75R16	114T	OWL	600A B	13	31.7	10.5	14.1	408
	P215/70R16	99S	BL	600A B	12	27.9	8.7	12.6	463
	P225/70R16	101T	BL	600A B	13	28.4	9.0	12.8	454
	P225/70R16	101T	OWL	600A B	13	28.4	9.0	12.8	454
	P235/70R16	104T	BL	600A B	13	29.0	9.4	13.1	445
	P235/70R16	104T	OWL	600A B	13	29.0	9.4	13.1	445
	P245/70R16	106S	BL	600A B	13	29.5	9.8	13.3	437
	P245/70R16	106S	OWL	600A B	13	29.5	9.8	13.3	437
	P255/70R16	109S	BL	600A B	13	30.1	10.2	13.5	429
	P255/70R16	109S	OWL	600A B	13	30.1	10.2	13.5	429
	P265/70R16	111T	OWL	600A B	13	30.6	10.7	13.7	421
255/65R16	109H	BL	600A A	13	29.1	10.2	13.1	444	
17	P235/75R17	108S	BL	600A B	13	30.9	9.3	13.9	418
	P255/70R17	110S	BL	600A B	13	31.1	10.2	14.0	415
	P265/70R17	113S	OWL	600A B	13	31.5	10.7	14.2	409
	P285/70R17	117T	BL	600A B	13	32.8	11.5	14.6	394
	P235/65R17	103H	BL	600A A	12	29.1	9.4	13.2	444
	P245/65R17	105T	BL	600A B	13	29.4	9.8	13.4	438
	P245/65R17	105T	OWL	600A B	13	29.5	9.8	13.4	437
18	P265/70R18	114S	BL	600A B	13	32.6	10.7	14.7	395
	285/60R18	XL 120S	BL	600A B	14	31.5	11.5	14.2	410
	255/55R18	XL 109H	BL	600A A	13	29.0	10.4	13.3	445
20	P245/60R20	107T	BL	600A B	13	31.6	9.8	14.5	409
	305/50R20	XL 120T	BL	600A B	14	32.0	12.4	14.7	403

LT and Flotation Sizes

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
15	LT235/75R15	104S	BL	6-C	16	28.9	9.3	12.9	447
	30x9.50R15LT	104S	OWL	6-C	16	29.5	9.4	13.2	437
	31x10.50R15LT	109S	OWL	6-C	16	30.5	10.6	13.5	423
16	LT215/85R16	115Q	BL	10-E	15	30.4	8.5	13.6	425
	LT235/85R16	120R	BL	10-E	16	31.7	9.3	14.1	407
	LT245/75R16	108S	BL	6-C	16	30.5	9.8	13.6	424
	LT265/75R16	112T	BL	6-C	16	31.7	10.5	14.1	408
	LT285/75R16	126R	BL	10-E	17	32.8	11.3	14.6	393
LT285/75R16	126R	OWL	10-E	17	32.8	11.3	14.6	393	

continued ...

LT and Flotation Sizes - continued

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
17	LT255/80R17	121/118R	BL	10-E	16	33.1	10.0	14.8	390
	LT285/70R17	121S	OWL	10-E	16	32.8	11.5	14.6	394
18	LT275/70R18	125S	OWL	10-E	16	33.2	11.0	14.9	389
	LT255/65R18	120/117S	BL	10-E	16	31.1	10.2	14.1	416
	LT275/65R18	113T	BL	6-C	16	32.1	11.0	14.5	402
	LT275/65R18	113T	OWL	6-C	16	32.1	11.0	14.5	402
	LT275/65R18	123S	OWL	10-E	16	32.1	11.0	14.5	402



"Millennium" warranty: - 100,000 km warranty on P-metric sizes.
 - 80,000 km warranty on LT and Flotation sizes.
 - 5 year workmanship and materials.

All weather sizes

OPEN COUNTRY[®] A/T II

P-METRIC

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
16	P245/75R16	109T	BL	600A B	13	30.5	9.8	13.6	424
	265/70R16	112T	BL	600A B	13	30.6	10.7	13.7	421
17	P245/70R17	108T	BL	600A B	13	30.6	9.8	13.8	423
	P265/70R17	113S	BL	600A B	13	31.7	10.7	14.2	408
	P265/65R17	110T	BL	600A B	13	30.6	10.7	13.8	423
18	P255/70R18	112T	BL	600A B	13	32.1	10.2	14.5	402
	P265/65R18	112H	BL	600A B	13	31.5	10.7	14.3	409
	275/65R18	116T	BL	600A B	13	32.1	11.0	14.5	402
	265/60R18	110T	BL	600A B	13	30.5	10.7	13.9	423
20	P275/60R20	114T	BL	600A B	13	33.0	11.0	15.1	391
	275/55R20	113S	BL	600A B	13	31.9	11.2	14.6	405
22	285/45R22	XL 114H	BL	600A A	14	32.1	11.2	14.9	402

LT AND FLOTATION

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
16	LT225/75R16	115/112Q	BL	10-E	15	29.3	8.8	13.2	441
	LT245/75R16	120/116S	BL	10-E	16	30.5	9.8	13.7	424
	LT265/75R16	123/120Q	BL	10-E	16	31.7	10.5	14.1	408
17	LT235/80R17	120/117R	BL	10-E	16	31.8	9.3	14.3	406
	LT245/75R17	121/118S	BL	10-E	16	31.5	9.8	14.1	410
	LT245/70R17	119/116R	BL	10-E	16	30.6	9.8	13.8	423
	LT265/70R17	121/118S	BL	10-E	16	31.7	10.7	14.2	408
	LT285/70R17	121/118S	BL	10-E	16	32.8	11.5	14.6	394
	LT265/70R18	124/121S	BL	10-E	16	32.6	10.7	14.7	396
18	LT275/70R18	125/122S	BL	10-E	16	33.2	11.0	14.9	389
	LT275/65R18	123/120S	BL	10-E	16	32.1	11.0	14.5	402
	LT275/65R20	126/123S	BL	10-E	16	34.1	11.0	15.5	379
20	LT265/60R20	121/118S	BL	10-E	16	32.5	10.7	14.9	397
	LT285/60R20	125/122R	BL	10-E	16	33.5	11.5	15.2	386



"Millennium" warranty:
 - 100,000 km warranty on P-metric sizes.
 - 80,000 km warranty on LT and Flotation sizes.*
 - 5 year workmanship and materials.

Xtreme Sizes

OPEN COUNTRY[®] A/T II XTREME

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
16	LT295/75R16	128R	BL	10-E	17	33.4	11.6	14.8	387
	LT315/75R16	127R	BL	10-E	17	34.6	12.3	15.2	373
	LT305/70R16	124R	BL	10-E	17	32.8	12.2	14.6	393
17	LT285/75R17	121S	BL	10-E	17	33.9	11.3	15.1	381
	LT305/70R17	121R	BL	10-E	17	33.9	12.2	15.1	381
	35x12.50R17LT	121R	BL	10-E	17	34.5	12.5	15.3	374
18	LT285/75R18	129S	BL	10-E	17	34.8	11.3	15.6	370
	LT295/70R18	129S	BL	10-E	16	34.3	11.8	13.4	376
	LT285/65R18	125S	BL	10-E	17	32.6	11.5	14.7	396
	LT325/65R18	127R	BL	10-E	17	34.6	13.0	15.5	373
	LT325/60R18	124S	BL	10-E	17	33.3	13.0	15.0	387
	33x12.50R18LT	122Q	BL	12-F	17	32.5	12.5	14.7	397

continued ...

XL - Extra Load

Xtreme Sizes - continued

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
18	35x12.50R18LT	123R	BL	10-E	17	34.5	12.5	15.4	374
	35x12.50R18LT	128Q	BL	12-F	17	34.5	12.5	15.4	374
20	LT295/65R20	129S	BL	10-E	17	35.1	11.8	13.7	368
	LT295/60R20	126S	BL	10-E	16	33.9	11.8	13.2	380
	LT325/60R20	126R	BL	10-E	17	35.4	13.0	16.0	365
	LT285/55R20	122S	BL	10-E	16	32.4	11.7	14.8	399
	LT295/55R20	123S	BL	10-E	16	32.8	12.2	12.8	394
	LT305/55R20	121S	BL	10-E	16	33.2	12.4	15.2	388
	LT305/55R20	125Q	BL	12-F	16	33.2	12.4	15.2	388
	33x12.50R20LT	119Q	BL	12-F	17	32.5	12.5	14.9	397
	35x12.50R20LT	121R	BL	10-E	17	34.5	12.5	15.7	374
	35x12.50R20LT	125Q	BL	12-F	17	34.5	12.5	15.7	374
	35x13.50R20LT	126Q	BL	12-F	17	34.5	13.6	15.7	374
22	LT325/50R22	122R	BL	10-E	17	34.8	13.2	16.0	370
	33x12.50R22LT	114Q	BL	12-F	16	32.5	12.5	15.1	397
	35x12.50R22LT	121Q	BL	12-F	16	34.5	12.5	15.9	374
	37x12.50R22LT	127Q	BL	12-F	17	36.5	12.5	16.7	354

The Open Country A/T II Xtreme sizes are not eligible for the mileage warranty or 30 day trial offer.

"Millennium" warranty: - 5 year workmanship and materials.

ALL WEATHER

OPEN COUNTRY C/T 

PINNED FOR STUDS

Stud -TSMI #15

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
16	LT215/85R16	115/112Q	BL	10-E	17	30.4	8.5	13.6	424
	LT235/85R16	120/116Q	BL	10-E	18	31.7	9.3	14.1	407
	LT225/75R16	115/112Q	BL	10-E	17	29.3	8.8	13.2	441
	LT245/75R16	120Q	BL	10-E	18	30.7	9.8	13.7	420
	LT265/75R16	123/120Q	BL	10-E	18	31.7	10.5	14.1	408
	LT285/75R16	116/113Q	BL	6-C	18	32.8	11.3	14.6	393
17	LT235/80R17	120Q	BL	10-E	18	32.0	9.3	14.4	403
	LT225/75R17	116/113Q	BL	10-E	17	30.3	8.8	13.7	426
	LT245/75R17	121Q	BL	10-E	18	31.7	9.8	14.2	407
	LT245/70R17	119Q	BL	10-E	18	30.8	9.8	13.9	419
	LT265/70R17	121Q	BL	10-E	18	31.9	10.7	14.3	405
	LT285/70R17	121Q	BL	10-E	18	33.0	11.5	14.7	391
	35x12.50R17LT	121Q	BL	10-E	19	34.8	12.5	15.4	371
18	LT265/70R18	124Q	BL	10-E	18	32.9	10.7	14.8	393
	LT275/70R18	125Q	BL	10-E	18	33.4	11.0	15.0	386
	LT275/65R18	123Q	BL	10-E	18	32.3	11.0	14.6	399
	35x12.50R18LT	123Q	BL	10-E	19	34.8	12.5	15.5	371
20	LT275/65R20	126Q	BL	10-E	18	34.3	11.0	15.6	376
	LT265/60R20	121Q	BL	10-E	18	32.8	10.7	15.0	394
	LT285/60R20	125/122Q	BL	10-E	18	33.5	11.5	15.2	386
	LT275/55R20	115Q	BL	8-D	18	32.1	11.2	14.7	402
	LT285/55R20	122Q	BL	10-E	18	32.6	11.7	14.9	396
	35x12.50R20LT	121Q	BL	10-E	19	34.8	12.5	15.8	371

"Millennium" warranty: - 5 year workmanship and materials.

OPEN COUNTRY R/T

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
15	LT265/75R16	123/120Q	BL	10-E	16	31.9	10.5	14.2	405
	LT285/75R16	126/123Q	BL	10-E	16	32.8	11.3	14.6	393
16	LT315/75R16	127/124Q	BL	10-E	16	34.6	12.3	15.2	373
	LT305/70R16	124/121Q	BL	10-E	16	32.8	12.2	14.6	393
	LT255/80R17	121/118Q	BL	10-E	16	33.1	10.0	14.8	390
	LT285/70R17	121/118Q	BL	10-E	16	33.0	11.5	14.7	391
17	LT295/70R17	121/118Q	BL	10-E	16	33.3	11.8	14.9	388
	35x12.50R17LT	121Q	BL	10-E	19	34.8	12.5	15.4	371
	37x12.50R17LT	124Q	BL	8-D	19	36.8	12.5	16.2	351
	37x13.50R17LT	121Q	BL	8-D	19	36.8	13.6	16.2	351
	LT285/75R18	129/126Q	BL	10-E	16	34.8	11.3	15.6	370
18	LT275/70R18	125/122Q	BL	10-E	16	33.2	11.0	14.9	389
	LT285/65R18	125/122Q	BL	10-E	16	32.8	11.5	14.8	394
	LT285/60R18	122/119Q	BL	10-E	16	31.5	11.5	14.2	410
	33x12.50R18LT	118Q	BL	10-E	19	32.8	12.5	14.8	394
	35x12.50R18LT	123Q	BL	10-E	19	34.8	12.5	15.5	371
	37x13.50R18LT	124Q	BL	8-D	19	36.8	13.6	16.3	351

continued ...

Sizes - continued

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
20	LT275/65R20	126/123Q	BL	10-E	16	34.1	11.0	15.5	379
	LT285/60R20	125/122Q	BL	10-E	16	33.5	11.5	15.2	386
	LT315/60R20	125/122Q	BL	10-E	16	34.9	12.7	15.8	370
	LT325/60R20	126/123Q	BL	10-E	16	35.4	13.0	16.0	365
	LT285/55R20	122/119Q	BL	10-E	16	32.4	11.7	14.8	399
	LT295/55R20	123/120Q	BL	10-E	16	32.8	12.2	15.0	394
	LT305/55R20	121/118Q	BL	10-E	16	33.2	12.4	15.2	388
	LT305/55R20	125/122Q	BL	12-F	16	33.2	12.4	15.2	388
	33x12.50R20LT	114Q	BL	10-E	19	32.8	12.5	15.0	394
	35x12.50R20LT	121Q	BL	10-E	19	34.2	12.5	15.8	371
	35x12.50R20LT	125Q	BL	12-F	19	34.8	12.5	15.8	372
	35x13.50R20LT	121Q	BL	10-E	19	34.8	13.6	15.8	371
	37x12.50R20LT	126Q	BL	10-E	19	36.8	12.5	16.5	351
	37x13.50R20LT	127Q	BL	10-E	19	36.8	13.6	16.5	351
22	35x12.50R22LT	117Q	BL	10-E	19	34.8	12.5	16.0	371
	37x12.50R22LT	123Q	BL	10-E	19	36.8	12.5	16.8	351
	37x13.50R22LT	123Q	BL	10-E	19	36.8	13.6	16.8	351

"Millennium" warranty:
- 5 year workmanship and materials.

OPEN COUNTRY M/T

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
15	31x10.50R15LT	109Q	BL	6-C	19	31.1	10.7	14.5	415
	33x10.50R15LT	114P	BL	6-C	19	32.8	10.9	15.3	393
	33x12.50R15LT	108P	BL	6-C	21	33.1	12.8	15.4	390
	33x13.50R15LT	109Q	BL	6-C	21	33.1	13.9	15.4	390
	35x13.50R15LT	114Q	BL	6-C	21	34.8	14.4	15.2	370
	37x14.50R15LT	120Q	BL	6-C	21	36.7	15.6	17.0	352
16	LT235/85R16	120P	BL	10-E	18	32.0	9.4	14.9	403
	LT255/85R16	123P	BL	10-E	19	33.5	10.2	15.6	385
	LT245/75R16	120P	BL	10-E	18	30.8	10.0	14.3	419
	LT265/75R16	123P	BL	10-E	19	31.9	10.8	14.8	405
	LT285/75R16	126P	BL	10-E	19	33.0	11.2	15.4	390
	LT315/75R16	127Q	BL	10-E	21	34.9	12.9	16.2	370
	LT305/70R16	124P	BL	10-E	20	33.1	12.2	15.4	390
	LT385/70R16	130Q	BL	8-D	21	37.7	15.6	17.5	342
17	LT255/75R17	111Q	BL	6-C	18	32.3	10.0	14.5	400
	LT285/75R17	121P	BL	10-E	19	34.1	11.6	15.9	378
	LT265/70R17	121P	BL	10-E	19	32.0	10.8	14.9	403
	LT285/70R17	121P	BL	10-E	19	33.0	11.5	12.9	391
	LT295/70R17	128P	BL	10-E	19	33.5	12.0	15.6	385
	LT315/70R17	121Q	BL	10-E	20	34.6	12.7	15.4	373
	33x12.50R17LT	120Q	BL	10-E	21	32.8	12.5	14.6	394
	35x12.50R17LT	125Q	BL	10-E	21	34.8	13.2	16.2	370
	37x12.50R17LT	124Q	BL	8-D	21	36.8	12.5	16.2	351
	37x13.50R17LT	131Q	BL	10-E	21	37.0	14.6	17.2	348
40x13.50R17LT	121Q	BL	6-C	21	39.7	14.4	18.5	325	
18	LT285/75R18	129P	BL	10-E	19	35.1	11.6	16.3	367
	LT275/70R18	125P	BL	10-E	19	33.6	11.0	15.6	383
	LT285/70R18	127Q	BL	10-E	19	34.1	11.4	15.9	378
	LT295/70R18	129P	BL	10-E	19	34.5	11.8	13.5	374
	LT315/70R18	127Q	BL	10-E	21	35.7	13.0	16.6	361
	LT275/65R18	123P	BL	10-E	19	32.3	11.0	12.6	399
	33x12.50R18LT	118Q	BL	10-E	21	33.0	12.7	15.3	391
	33x12.50R18LT	122Q	BL	12-F	21	32.8	12.5	14.8	394
	35x12.50R18LT	123Q	BL	10-E	21	35.0	13.2	15.6	368
	35x12.50R18LT	128Q	BL	12-F	21	34.8	12.5	15.5	371
	37x13.50R18LT	124Q	BL	8-D	21	37.0	14.2	17.2	348
	38x13.50R18LT	126Q	BL	8-D	21	37.7	14.4	17.5	342
38x15.50R18LT	128Q	BL	8-D	21	37.7	15.9	16.7	342	
20	LT275/65R20	126P	BL	10-E	19	34.5	11.0	16.1	373
	LT295/65R20	129P	BL	10-E	19	35.4	11.8	13.8	365
	LT285/60R20	125/122Q	BL	10-E	19	33.5	11.5	15.3	386
	LT295/60R20	126P	BL	10-E	19	34.2	11.8	15.5	378
	LT315/60R20	125Q	BL	10-E	21	35.0	12.6	16.3	368
	LT275/55R20	115P	BL	8-D	19	32.1	11.2	12.5	402
	LT295/55R20	123P	BL	10-E	19	33.0	12.2	12.9	391
	LT305/55R20	125Q	BL	12-F	20	33.5	12.4	15.3	386
	33x12.50R20LT	114Q	BL	10-E	21	33.0	12.6	15.3	391
	33x12.50R20LT	119Q	BL	12-F	21	32.8	12.5	15.0	394
	35x12.50R20LT	121Q	BL	10-E	21	35.0	13.0	16.3	368
	35x12.50R20LT	125Q	BL	12-F	21	34.8	12.5	15.8	371

continued ...

Sizes - continued

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
20	35x13.50R20LT	126Q	BL	12-F	21	34.8	13.6	15.8	371
	37x12.50R20LT	126Q	BL	10-E	21	36.8	12.5	16.5	351
	37x13.50R20LT	127Q	BL	10-E	21	37.0	14.0	17.2	348
	38x13.50R20LT	124Q	BL	8-D	21	37.7	14.4	17.5	342
	38x15.50R20LT	125Q	BL	8-D	21	37.7	15.9	17.5	342
	40x15.50R20LT	130Q	BL	8-D	21	39.7	15.9	18.5	324
22	LT325/50R22	122Q	BL	10-E	20	35.1	13.2	16.1	368
	33x12.50R22LT	109Q	BL	10-E	19	33.0	12.4	15.3	391
	33x12.50R22LT	114Q	BL	12-F	19	32.8	12.5	15.2	394
	35x12.50R22LT	117Q	BL	10-E	21	35.0	12.8	16.3	368
	35x12.50R22LT	121Q	BL	12-F	21	34.8	12.5	16.0	371
	37x12.50R22LT	127Q	BL	12-F	21	36.8	12.5	16.8	351
	37x13.50R22LT	123Q	BL	10-E	21	37.0	14.0	17.2	348
24	40x15.50R22LT	127Q	BL	8-D	21	39.7	15.9	18.5	324
	37x13.50R24LT	120Q	BL	10-E	21	37.0	13.6	17.2	349
	40x15.50R24LT	128P	BL	10-E	21	39.8	15.4	18.1	325

"Millennium" warranty: - 5 year workmanship and materials.

ALL WEATHER

M-55



PINNED FOR STUDS

Stud -TSMI #15

	SIZE	SD	SW		1/32"	OD	OW	SLR	RV
15	LT215/75R15	100Q	BL	6-C	17	28.0	8.7	12.6	461
	LT235/75R15	104Q	BL	6-C	18	28.9	9.3	12.9	447
16	LT215/85R16	▲ 115Q	BL	10-E	17	30.7	8.7	13.8	420
	LT235/85R16	▲ 120Q	BL	10-E	18	32.0	9.3	14.2	404
	LT255/85R16	▲ 123Q	BL	10-E	18	33.4	10.4	14.8	387
	LT225/75R16	▲ 115Q	BL	10-E	17	29.4	8.7	13.2	438
	LT245/75R16	▲ 120Q	BL	10-E	18	30.8	9.8	13.8	419
	LT265/75R16	▲ 123Q	BL	10-E	18	32.0	10.8	14.2	403
	LT285/75R16	▲ 126Q	BL	10-E	19	33.2	11.2	14.7	389
17	LT235/80R17	▲ 120Q	BL	10-E	18	32.0	9.3	14.4	403
	LT245/75R17	▲ 121Q	BL	10-E	18	31.9	9.7	14.3	404
	LT265/70R17	▲ 121Q	BL	10-E	18	32.0	10.6	14.4	403
	LT285/70R17	121Q	BL	10-E	19	33.1	11.4	14.8	389
18	LT265/70R18	▲ 124/121Q	BL	10-E	18	33.0	10.6	12.9	391
	LT275/70R18	▲ 125Q	BL	10-E	19	33.6	11	15.1	385
	LT275/65R18	▲ 123/120Q	BL	10-E	19	32.4	11	12.6	398

* while supplies last

	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
16	LT245/75R16	120Q	BL	10-E	18	30.8	9.8	13.8	419
	LT285/75R16	126Q	BL	10-E	19	33.2	11.2	14.7	389
18	LT275/65R18	123/120Q	BL	10-E	19	32.4	11.0	12.6	398

"Millennium" warranty: - 5 year workmanship and materials.

WINTER

OPEN COUNTRY WLT1



	SIZE	SD	SW		1/32"	OD	OW	SLR	RPK
16	LT215/85R16	115Q	BL	10-E	16	30.4	8.9	13.6	424
	LT235/85R16	120Q	BL	10-E	16	31.9	9.3	14.2	405
	LT225/75R16	115Q	BL	10-E	16	29.4	8.9	13.2	440
	LT245/75R16	120Q	BL	10-E	16	30.6	9.9	13.7	423
	LT265/75R16	123Q	BL	10-E	17	31.7	10.7	14.1	407
	LT285/75R16	122Q	BL	10-E	17	32.8	11.4	14.6	393
17	LT235/80R17	120Q	BL	10-E	16	31.9	9.4	14.3	404
	LT225/75R17	116Q	BL	10-E	16	30.4	8.9	13.7	425
	LT245/75R17	121Q	BL	10-E	16	31.6	9.8	14.2	409
	LT245/70R17	119Q	BL	10-E	16	30.6	9.7	13.8	421
	LT265/70R17	121Q	BL	10-E	17	31.8	10.7	14.3	406
	LT285/70R17	121Q	BL	10-E	17	32.8	11.5	14.7	393
18	LT265/70R18	124Q	BL	10-E	17	32.6	10.7	12.7	395
	LT275/70R18	125Q	BL	10-E	17	33.3	10.9	15.0	388
	LT275/65R18	123Q	BL	10-E	17	32.3	10.9	14.6	400
20	LT275/65R20	126Q	BL	10-E	17	34.3	10.5	15.6	376
	LT265/60R20	121Q	BL	10-E	17	32.5	10.7	14.9	397

"Millennium" warranty: - 5 year workmanship and materials.

Tire data subject to change. Visit toyotires.ca for current data.

TOYO TIRES

Date:

Size:

Price:

Notes:

For warranty details and directions on registering your new TOYO Passenger, Light Truck, Van or SUV tires be sure to ask for your TOYO TIRES Millennium Warranty Booklet at time of purchase.

Toyo Tire Canada Inc.

1-877-682-TOYO

www.toyotires.ca



[/toyotirescanada](#)



Mobile bar code - scan for more information on this product, videos, specials and features.

Mobile bar code reader - Visit your mobile app store for a free reader.



Go Green
Printed on recycled paper