



# M137™

## Long-Haul Steer Tire

Over the highway steer tire designed for use in long haul applications



STEER AXLE - ALL POSITION

CUSTOMER BENEFIT	PRODUCT FEATURES
Resists Irregular Wear for Longer Tread Life	<ul style="list-style-type: none"> <li>E-balance design provides even contact pressure distribution across the tread surface resulting in even wear and long life.</li> <li>Top Differential Groove™ and tread depth are optimized to minimize irregular wear and to maximize miles per 32nd.</li> </ul>
Traction	<ul style="list-style-type: none"> <li>Deep sipes and multi-pitch grooves enhance wet traction.</li> <li>Four straight grooves sustain water drainage.</li> </ul>
Casing Durability and Enhanced Retreadability	<ul style="list-style-type: none"> <li>Special cap and base tread compound reduces heat at the belt edge and excessive heat build-up inside the tire structure.</li> <li>E-balance profile minimizes growth of the tread profile and maintains uniform and flatter tread radius for the entire life of the casing.</li> </ul>

TIRE SIZE	PLY	L.I./S.R. LOAD INDEX SPEED RATING	CODE	WEIGHT (Lbs/ Kg)	TREAD (32"/ mm)	RIM DESIGN/ ALT. (inches)	INFLATED DIAMETER WIDTH (in./ mm)	STATIC LOADED RADIUS WIDTH (in./ mm)	MAX TIRE LOAD SINGLE (Lbs@PS/ Kg@KPa)	MAX TIRE LOAD DUAL (Lbs@PS/ Kg@KPa)	REVS PER (km/ mile)	MAX SPEED (mph/ kph)		
11R22.5	14G	144/142L	547030	51.7 114.0	15 12	8.25 7.50-8.25	40.9 1040	11.2 284	18.4 468	12.2 310	6175@105 2799@725	5840@105 2647@725	315 507	75 120
11R22.5	16H	146/143L	546990	51.5 113.5	15 12	8.25 7.50-8.25	41.1 1043	11.1 282	18.5 470	12.1 307	6610@120 2997@829	6005@120 2722@829	314 506	75 120
11R24.5	14G	146/143L	547050	55.1 121.4	15 12	8.25 7.50-8.25	43.0 1091	11.2 284	19.4 494	12.2 310	6610@105 2996@725	6005@105 2722@725	301 484	75 120
11R24.5	16H	149/146L	546980	55.0 121.3	15 12	8.25 7.50-8.25	43.1 1094	11.1 282	19.5 495	12.1 307	7160@120 3242@829	6610@120 2997@829	300 482	75 120
<b>LOW PROFILE</b>														
295/75R22.5	14G	144/141L	547010	49.9 110.0	15 12	8.25 8.25-9.00	39.8 1011	11.3 286	18.0 457	12.3 312	6175@110 2799@760	5675@110 2573@760	324 522	75 120
295/75R22.5	16H	146/143L	547000	50.4 111.0	15 12	8.25 8.25-9.00	40.0 1015	11.1 282	18.1 459	12.1 307	6610@120 2996@829	6005@120 2722@829	323 520	75 120
285/75R24.5	14G	144/141L	547020	52.0 114.7	15 12	8.25 8.25	41.2 1047	11.0 280	18.8 477	12.0 305	6175@110 2799@760	5675@110 2573@760	313 504	75 120
285/75R24.5	16H	147/144L	547070	52.5 115.7	15 12	8.25 8.25	41.1 1043	10.8 275	18.7 475	11.8 300	6780@120 3073@829	6175@120 2799@829	314 506	75 120

The speed symbol does not imply that a vehicle can be safely operated at the indicated speed if the tires are overloaded, underinflated, mis-applied, damaged, or fatigued from prior use.

### APPLICATION SUMMARY



APPLICATION	RECOMMENDED	SUITABLE
LONG-HAUL	STEER	TRAILER