



M171+™

Super Regional Steer Tire

The M171+ super regional steer tire complements the M671A+ super regional drive tire. Working together, these tires are specifically designed to provide long wear, optimal fuel efficiency, and dependable traction, within demanding 500-mile (800-km) radius operations.



CUSTOMER BENEFIT	PRODUCT FEATURES
Improved Tread Compound	• Maximize removal miles while maintaining low rolling resistance and traction
Maximum Fuel Efficiency	• Nano Balance Technology increases fuel efficiency and provides long, even wear
Excellent Removal Miles	• An advanced tread design provides good traction and a smooth ride • A wide belt package minimizes the growth of the tread profile and maintains a flatter tread radius
Exceptional and Casing Durability	• E-balance technology retains the tread profile while reducing strain at the bead area and belt edge • Stone ejectors prevent casing damage • Steel chafer bead improves durability and retreadability

TIRE SIZE	PLY	L.I./S.R. LOAD INDEX SPEED RATING	CODE	WEIGHT (Lbs/ Kg)	TREAD (32"/ mm)	RIM DESIGN/ ALT. (inches)	INFLATED DIAMETER (in./ mm)	INFLATED WIDTH (in./ mm)	STATIC LOADED RADIUS (in./ mm)	STATIC LOADED WIDTH (in./ mm)	MAX TIRE LOAD SINGLE (Lbs@PS/ Kg@KPa)	MAX TIRE LOAD DUAL (Lbs@PS/ Kg@KPa)	REVS PER MILE	MAX SPEED (mph/ kph)
295/75R22.5	14G	144/141L	520060	115.3 52.3	20 16	8.25 8.25-9.0	40.1 1019	11.1 282	18.7 474	12.1 307	6175@110 2800@760	5675@110 2575@760	321 518	75 120
295/75R22.5	16H	149/146L	520050	116.4 52.8	20 16	8.25 8.25-9.0	40.1 1019	11.1 282	18.7 474	12.1 307	7160@123 3250@825	6610@123 3000@825	321 518	75 120
11R22.5	14G	144/142L	520080	121.3 55.0	20 16	8.25 7.5-8.25	41.5 1054	11.1 282	19.3 307	12.2 309	6175@105 2800@720	5840@105 2650@720	311 501	75 120
11R22.5	16H	146/143L	520070	122.4 55.5	20 16	8.25 7.5-8.25	41.5 1054	11.1 282	19.3 490	12.2 309	6610@120 3000@825	6005@120 2725@825	311 501	75 120

The speed symbol does not imply that a vehicle can be safely operated at the indicated speed if the tires are overloaded, underinflated, mis-applied, damaged or fatigued from prior use.

APPLICATION SUMMARY



APPLICATION	RECOMMENDED	SUITABLE
REGIONAL	STEER	DRIVE, TRAILER