

# TOYO TIRES®

## M655™

Regional, Urban, On/Off-Road,  
Drive/All-Position Tire



RESIST IRREGULAR  
WEAR

3-PEAK MOUNTAIN  
SNOWFLAKE

CASING DURABILITY  
AND ENHANCED  
RETREADABILITY

RESISTS CHUNKING  
AND CHIPPING

APPLICATION	RECOMMENDED	SUITABLE
REGIONAL	DRIVE	-
URBAN	DRIVE	-
ON/OFF ROAD	DRIVE	STEER

**5** Years  
Limited Warranty

## FEATURES AND BENEFITS

- The Toyo M655 has been created to meet the demands of the modern mixed service commercial customer.
- The M655 was designed and tested year round, in harsh Canadian conditions, to ensure your fleet keeps moving. Maximizing uptime, to save you money.
- Wider groove and wall-angle prevent stone holding. Stone ejector in all grooves prevents stone drilling and reduce casing damage by stone.
- M655 Power Line will offer our fleet customers a single powerline On/Off commercial traction pattern for all construction vocational applications. Targeted specifically at fleet business.



## SIZES AND SPECIFICATIONS

TIRE SIZE	PLY	LOAD/ SPEED	CODE	WEIGHT (Lbs/Kg)	TREAD (32"mm)	RIM DESIGN/ ALT. (INCHES)	INFLATED DIAMETER (In./mm)	INFLATED WIDTH (In./mm)	STATIC LOADED RADIUS (In./mm)	STATIC LOADED WIDTH (In./mm)	MAX TIRE LOAD SINGLE (Lbs@PS/Kg@ KPa)	MAX TIRE LOAD DUAL (Lbs@PS/ Kg@KPa)	REVS PER (Km/ Mile)	MAX SPEED (Mph/ Kph)
225/70R19.5	14-G	128/126N	556640	70.3 31.9	20 16	6.0 6.00-6.75	32.3 821	8.5 217	14.8 375	9.3 237	3970@110 1800@760	3750@110 1701@760	400 643	87 140
245/70R19.5	16-H	136/134N	556650	81.8 37.1	21 16	7.5 6.75-7.50	33.5 850	9.9 251	15.2 386	10.8 274	4940@120 2240@829	4675@120 2120@829	386 621	87 140
265/70R19.5	14-G	140/138N	111300	84.0 38.1	20 15.9	7.5 7.50-8.25	34.5 877	10 254	16.1 408	10.8 274	5510@112 2499@772	5205@112 2361@772	374 602	87 140
295/75R22.5	14-G	144/141L	556810	122.2 55.5	28 22.3	9 8.25-9.00	40.7 1034	11.1 282	18.9 481	12.1 307	6675@110 2801@758	5675@110 2574@758	317 510	75 120
11R22.5	16-H	146/143L	556790	129.0 58.5	28 22.3	8.25 7.50-8.25	42.1 1069	11.1 282	19.6 497	12.2 309	6610@120 2998@827	6005@120 2724@827	307 494	75 120
11R24.5	16-H	149/146L	556800	138.9 63.0	28 22.3	8.25 7.50-8.25	44.0 1118	11.1 282	20.5 420	12.2 309	7160@120 3248@827	6610@120 2998@827	293 472	75 120

Bold designates measuring rim width

Load ID Range: F = 12, G = 14, H = 16, J = 18, L = 20, M = 22

Speed Rating: J = 62 mph, K = 68 mph, L = 75 mph, M = 81 mph, N = 87 mph

## COMPARES TO

Michelin X Multi D, XDS2  
Bridgestone M770, M799  
Goodyear G182 RSD  
BFGoodrich Route Control D

Continental HDR2+  
Yokohama 715R  
Hankook DH06  
Firestone FD711